



Technical data

Substance		
Component	Stable aluminium pressure cylinder, ergonomic nylon handle	
Property	Regulation	Value
Length		445 mm ; 17 1/2"
Width		276 mm ; 10 7/8"
Height		83 mm ; 3 1/4"
Weight		1.6 kg ; 3.53 lbs

Application

For particularly quick and easy application of the AEROSANA VISCONN and AEROSANA VISCONN FIBRE sealants from 600 ml foil cartridges onto smooth and rough mineral and non-mineral subsurfaces such as timber, wood fibreboards, OSB, stone, plaster, concrete etc.

For use with air compressors capable of up to 6.8 bar (100 psi), 300 l/min air flow.

Advantages

- ✓ Work more quickly: application and spreading of the sealant in a single working step
- ✓ Precise application of material: setting 1 for a line of sealant to close joints, setting 2 to spray over and seal surfaces
- ✓ Allows the technician to work with one hand
- ✓ No brush required
- ✓ Pressure: up to 6.8 bar (100 psi)

General conditions

The AEROFIXX device is connected to a compressor with a suction flow rate of >300 l/min. The pressure is set to 6 bar. All AEROSANA VISCONN products in 600 ml tubular bags can be applied using the AEROFIXX device. You can easily switch between line application and spray application by turning the spray head.



The information provided here is based on practical experience and the current state of knowledge. We reserve the right to make changes to the recommended designs and processing or to make alterations due to technical developments and associated improvements in the quality of our products. We would be happy to inform you of the current technical state of the art at the time you use our products.

Further information about the application and construction can be found in the pro clima planning documentation. For queries please call the pro clima technical hotline on +49 (0)6202 278245.

MOLL
bauökologische Produkte GmbH
Rheintalstraße 35 - 43
D-68723 Schwetzingen
Fon: +49 (0) 62 02 - 27 82.0
eMail: info@proclima.de

