# ComfoSense 67

The Zehnder ComfoSense 67 is a four position switch designed to enable the user to manually select the desired ventilation systems flow rate and provide system notifications.

## Key Benefits

(r) 4 separate ventilation flow rate options to select in 1 controller

(r) 7 day flow rate programmer

(r) Summer bypass indicator

(r) Frost protection indicator

(r) Service and Maintenance alert

(r) Clock function

(r) User menu access

(r) Installer menu access

(r) RF bridge to enable use of the CCRFZ controller

## Technical Specification

| Mounting options | Recessed / Surface |
|---|---|
| Supply voltage | Low voltage direct from the MVHR units PCB connector |
| IP rating | IP44 |
| Recommended cable | 4 core cable, 1mm Max. (up to 50 metres) |
| RAL colour | 9016 |

## Description / Product Code

Suitable for use with MVHR units:

| | |
|---|---|
| Zehnder ComfoAir 160 Luxe | 471218960 |
| Zehnder ComfoAir 160 Luxe with pre-heater | 471218915 |
| Zehnder ComfoAir 180 Luxe with pre-heater | 471212385 |
| Zehnder ComfoAir 200 Luxe with pre-heater, left handed | 471226310 |
| Zehnder ComfoAir 200 Luxe with pre-heater, right handed | 471226315 |

## Dimensions (recessed)

| Height | 80mm |
|---|---|
| Width | 80mm |
| Depth | 12mm |

## Dimensions (surface mounted)

| Height | 80mm |
|---|---|
| Width | 80mm |
| Depth | 48.5mm |

## Article

CCS