

Zehnder ComfoConnect PRO

Controls, Zehnder ComfoConnect PRO BMS interface for Zehnder ComfoAir Q350/450/600 and ComfoAir Flex 250/350

Product data sheet always the best climate





ComfoConnect PRO

Product code: 471 429 300



The Zehnder ComfoConnect PRO Modbus, Internet and app interface allows you to use the Zehnder ComfoControl app. The connection to the Zehnder device is wired via ComfoNET and LAN or wireless via Wi-Fi. Direct connection to a home automation system is also possible.

Key Benefits

- Automation protocols (Modbus RTU/TCP) with local / remote app control via cloud and technical support
- Digital security cryptographic keys, secure cloud platform and automatic software updates
- Compatible with a wide range of Zehnder ComfoNet II devices and accessories (Zehnder ComfoAir Q, Zehnder ComfoAir Flex, Zehnder ComfoSwitch C / ComfoSense C)

Technical Specification		Dimensions	
Supply voltage	Low voltage direct from the MVHR units ComfoNET connector	Dimensions (surface mounted)	
IP rating	IPX0	<u>Height</u> Width	133 mm 90 mm
Recommended cable	4 core cable, 1 mm Max. (up to 50 metres)	Depth	41 mm
RAL colour	Front: 9003 Back: 7024	Бериі	41111111
Maximum number per unit	1		
Wi-Fi	2.4 GHz / 5 GHz		
Ethernet	10/100 Mbit		
Connectors	RS232 RS485		
Communication protocols	Modbus TCP Modbus RTU		
Compatible smart home manufacturers	Loxone Smart Place		

Wiring





